



- » II3 D Ex tD A22 Tx IP66
- » TÜV NORD Statement Conformity Number TÜV 05 ATEX 2768X
- » Equipment and protective system intended for use in potentially explosive atmospheres [Zone 22] - Directive 94/9/EC
- » Compliance with Essential Health and Safety Requirements
- » IEC 60079-10-2



MVE STANDARD RANGE




DC DIRECT CURRENT - 3000 rpm



Wm (kgcm)	Model	RPM	Centrifugal Force (kg)	Weight (kg)	ELECTRICAL SPECIFICATIONS			CERTIFICATE
					Input Power (kW)	Nominal Current A max	Cable Gland	 II3D
1.02	MVE 50 DC 12	3000	50	4.4	0.08	6.6	M16	100°C
1.02	MVE 50 DC 24	3000	50	4.4	0.08	3.3	M16	100°C
4.17	MVE 202 DC 12	3000	200	7.2	0.16	13.3	M20	100°C
4.17	MVE 202 DC 24	3000	200	7.2	0.16	6.7	M20	100°C

To convert kg into Newton: $N = 9.81 \cdot kg$



DIMENSIONAL SPECIFICATIONS (mm)															
Model	Drawing	Size	C	M	A	B	ØG	Holes	D	E	F	H	I	L	N
MVE 50 DC 12	A	10	211	45	Multiple Footprint			4	130	136	12	48	94	121	85
					62-74	106	9								
MVE 50 DC 24	A	10	211	45	33	83-102	7	4	130	136	12	48	94	121	85
MVE 202 DC 12	G	23	218	53	Multiple Footprint			4	164	140	25	82	116	159	110
					62-74	106	9								
					65	140	13								
MVE 202 DC 24	G	23	218	53	115	135	11	4	164	140	25	82	116	159	110
					135	115	11								

NOTE: Dimensions with coarse degree of accuracy related to UNI 22768/1

This information is provided without warranty, representation, inducement or licence of any kind. It is accurate to the best OLI knowledge or is obtained from sources believed to be accurate. OLI therefore assumes no legal responsibility.